



L300m



L250m



# Lashing Webbing 2T

Lashing webbing is made to assume perfect stability of your heavy loads during their transport in container or truck.

Its presentation in the linear meter allows you to optimize its use cutting the lashing webbing following your needs.

Adapted buckles are also available to finish fitting, stabilization and necessary tightening.

## LASHING 2T - 300M - RIGID

- Woven polyester / reinforced
- Linear resistance : 2200 kg
- Maximum extension : 8 to 12%
- Width : 32 mm
- Meters in bag : 300m
- Weight bag : 11.4 kg
- Per unit (bag) or pallet of 12 bags

## SANGLE 2T - 250M - FLEXIBLE

- Woven polyester
- Linear resistance : 2000 kg (daN), breaking load as per EN12195 norm
- Lashing capacity = LC : 667 daN
- Width : 32 mm
- Meters in bag : 250m
- Weight bag : 9 kg
- Per unit (bag) or pallet of 16 bags

Associated products : OWB3030W Buckles or phosphated strapping buckles.

## information & contact

Mail : [contact@bjservicesisolation.com](mailto:contact@bjservicesisolation.com)  
Tél : 00 (33) 235 411 002  
43 rue des Drapiers  
76600 Le Havre, FRANCE



[www.isolationconteneurs.com](http://www.isolationconteneurs.com)