



Tarpaulin

For open top containers

(OT) Tailor-made

If you need to protect your goods inside an open-top container, you install a specific tarpaulin made for OT container. This tarpaulin is covering all container opened roof and prevent load from bad weather and curious.

In order to adapt to all different load heights which can be higher than container's one, those tarpaulins can be tailor-made so that you choose your own height. Eyelets and tir cable are always the same but tarpaulin height could differ, it is called «extra height».

Characteristics	ONE WAY 210GR/SQM	PVC 630GR/SQM
Material	Polyéthylène (HDPE)	PVC Polyester 1100 Dtex
Weaving	4.8 wires/cm	7 wires/cm
Finishing	UV Treatment	Opaque
Temperature resistance	-40°C / +70°C	-30°C / +70°C
Tear resistance (DIN 53363)	Wrap > ca 11 DaN Weft > ca 11 DaN	Wrap > ca 25 DaN Weft > ca 25 DaN
Tensile strenght (DIN 53354)	Wrap > ca 65 DaN/5 cm Weft > ca 5 DaN/5 cm	Wrap > 220 DaN/5 cm Weft > 180 DaN/5 cm
(IVK/PKT 14)	Stretching: 20%	Adhesion: ca 9 DaN/5 cm

Those tarpaulins can be made in two different quality :

- «ONE WAY» (OW), 210gr/m², universal type (not suitable for container owned by Hapag Lloyd), adjusted to 20'OT or 40'OT with requested height if «Extra». This quality, as named, is often used for single way trip and also often used to cover loads on Flat containers.
- «PVC 630gr/m²», universal type (not suitable for container owned by Hapag Lloyd), adjusted to 20'OT or 40'OT with requested height if «Extra». This quality is stronger and often used to dose OT containers which could be used several times.

information & contact

Mail : contact@bjservicesisolation.com
Tél : 00 (33) 235 411 002
43 rue des Drapiers
76600 Le Havre, FRANCE



www.isolationconteneurs.com